



"Tomorrow's Lighting Solutions Today"

Project Name: \_\_\_\_\_

Type: \_\_\_\_\_

Catalog #: \_\_\_\_\_

# LED Highbay Luminaires

- Warehouse • Manufacturing
- Distribution • Gymnasium

## Description

This LED Highbay and Lowbay fixture from GreenLine Industries is designed with today's most advanced LED technology. With power consumptions a fraction of standard HID or fluorescent fixtures and efficacies up to 116 lumens per watt, this is a fixture that provides the lowest cost per delivered lumen in the industry. With lumen packages ranging from 12,000 lumens (104w) all the way up to 48,000 lumens (406w) we can meet any application's needs. Mounting heights can range from under 15'- 60' in any warehouse, gymnasium, manufacturing, or industrial facility. Standard configurations come with a 5000K color temperature and the fixtures are cable ready for installation.



## Electrical / Lumen Configurations

Fixture Config.	Wattage	120/277v Amps	Lumens	Efficacy
2' - 2 module	104	.866/.38	13,336	133.77
2' - 4 module	206	1.72/.74	26,732	133.77
4' - 6 module	310	2.58/1.12	40,098	133.77
4' - 8 module	406	2.94/1.28	53,465	133.77

## LED Highbay

## Example Part Number

GLHBLED - 2 - 2 - MV/HV - 40 - OC - CL - AC-10

Number	Fixture Length	Lumens	Voltage	Color Temp	Options	Lens Options	Mounting Options
GLHB LED High Bay	2 = 2' 4 = 4'	2 = 2 4 = 4 6 = 6 8 = 8	MV= 120/277v HV= 347/480v	40=4000K 50=5000K	6' cord: C-6 10' cord: C-10 15' cord: C-15  Occupancy Sensor (OC)	Come with no lens  Clear Lens-CL Frosted Lens-FL	Air craft cable 6' AC-6 Air craft cable 10' AC-10 Pendent Mount - PM Wide distribution for lower mounting heights - W Heights Listed Ships with -N

# LED Highbay Luminaires

- Warehouse • Manufacturing
- Distribution • Gymnasium

Regulatory:
Recognized - UL8750 CAN/
CSA-C22.2 No. 250.13-12 / ETL Listed
RoHS Compliant

Notes:
CRI = > 82
Dry/Damp (IP-30)
Warranty : Limited 7 years

